



ISO Mounting Pad Dimensions

Dimensions: **inches** (millimeters)

Flanged type	d_1	d_2	d_3	d_4	h_1 max.	h_2 min.	Number of screws, studs or bolts
F03	1.81 (46)	.984 (25)	1.42 (36)	M5	.118 (3)	.315 (8)	4
F04	2.12 (54)	1.18 (30)	1.65 (42)	M5	.118 (3)	.315 (8)	4
F05	2.56 (65)	1.37 (35)	2 (50)	M6	.118 (3)	.354 (9)	4
F07	3.54 (90)	2.16 (55)	2.75 (70)	M8	.118 (3)	.472 (12)	4
F10	4.92 (125)	2.75 (70)	4.00 (102)	M10	.118 (3)	.590 (15)	4
F12	5.90 (150)	3.34 (85)	4.92 (125)	M12	.118 (3)	.708 (18)	4
F14	6.88 (175)	3.94 (100)	5.50 (140)	M16	.157 (4)	.945 (24)	4
F16	8.26 (210)	5.12 (130)	6.50 (165)	M20	.197 (5)	1.18 (30)	4
F25	11.81 (300)	7.87 (200)	10 (254)	M16	.197 (5)	.945 (24)	8
F30	13.78 (350)	9 (230)	11.75 (298)	M20	.197 (5)	1.18 (30)	8
F35	16.34 (415)	10.25 (260)	14 (356)	M30	.197 (5)	1.77 (45)	8
F40	18.70 (475)	11.81 (300)	16 (406)	M36	.315 (8)	2.12 (54)	8
F48	22 (560)	14.57 (370)	19 (483)	M36	.315 (8)	2.12 (54)	12
F60	27 (686)	18.50 (470)	23.75 (603)	M36	.315 (8)	2.12 (54)	20



WILLIAMS

VALVE CORPORATION

38-52 Review Ave. · Long Island City, NY 11101 · (Phone) 718-392-1660 · (Fax) 718-729-5106